



**Mallory Sonalert Products, Inc.**

Part #:

**SCE028LD3VC1B**

# Sales Outline Drawing

Revision:

**A**

## Specifications:

|                        |  |                           |                             |
|------------------------|--|---------------------------|-----------------------------|
| Sound Level Category:  | Loud   | Medium                    | Soft                        |
| Mode of Operation:     | Continuous   | Continuous                | Continuous                  |
| Loudness @ 2 FT:       | 85 to 95 dB(A) Typ.  | 75 to 85 dB(A) Typ.       | 65 to 75 dB(A) Typ.         |
| Frequency:             | 2900 ± 500 Hz  | 2900 ± 500 Hz             | 2900 ± 500 Hz               |
| Connection:            | T-BLOCK ONLY   | T-BLOCK; BLUE WIRE TO (-) | T-BLOCK; YELLOW WIRE TO (-) |
| Voltage Rating:        | 16 to 28 VDC   |                           |                             |
| Current Draw:          | 40mA MAX   |                           |                             |
| Housing Material:      | 6/6 Nylon, Color: Black  |                           |                             |
| Storage Temperature:   | -40° to +85° C   |                           |                             |
| Operating Temperature: | -40° to +85° C   |                           |                             |
| Panel Mounting:        | Recommended hole size is 1.25"(31.75mm). Thread front will fit standard 30mm(1.181") hole. |                           |                             |
| Knurled Nut:           | Used to attach part to panel. The max recommended torque is 10 in-lbs.                     |                           |                             |
| Weight (Typical):      | 1.6 oz (45g)   |                           |                             |
| NEMA 3R,4X, & 12:      | Approved with use of ACC03.  |                           |                             |
| cUL Recognition:       | cUL Recognized   |                           |                             |
| Options:               | Please contact factory.  |                           |                             |

## Dimensions: Inches (mm)

**ROHS Compliant**

