



DATE	DESCRIPTION	REV.
8.11.99	CHANGE AS PER ECN 99-056	A
6.8.05	CHANGE AS PER ECN 05-032	B
9.22.08	CHANGE AS PER ECN 08-162	C
12.15.09	CHANGE AS PER ECN 09-186	D
1.13.12	CHANGE AS PER ECN 12-006	E

Notes:

- Shell: Mat'l: Phosphor Bronze,
Finish: Tin Plate over Nickel Plate.
- Insulator: Glass Filled LCP
- Contacts: Mat'l: Phosphor Bronze
Finish: Contact Area -Gold Plate over Nickel Plate
Solder Tail - Tin Plate over Nickel Plate

Electrical Specifications

- Contact Resistance: 30 milliohms Max.
- Dielectric Withstanding Voltage: 500V AC
- Insulation Resistance : 1000 Mohms Min.
- Operating Temperature: -25°C to 85°C
- Durability min. : 1500 cycles.

THIS DOCUMENT IS THE PROPERTY OF KEYSTONE ELECTRONICS CORP. AND SHALL NOT BE REPRODUCED, DISTRIBUTED OR USED AS A BASIS FOR MANUFACTURE WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP.

KEYSTONE ELECTRONICS CORP.			
www.keystec.com • ASTORIA, N.Y. 11105-2017 • Tel (718) 956-8900			
PART NAME			
USB A-TYPE HORIZONTAL SOCKET			
MATERIAL			
AS NOTED			
FINISH		AS NOTED	
TOLERANCES	INCH	[MM]	CODE
DECIMAL	± .010	[± 0.25]	
ANGULAR	± 1°		C/M
DRN BY		DATE	DWG NO.
BOONE		6.18.98	
APP'D		SCALE	
LN		2.5X	
921			