## **HellermannTyton**

## **Specification Sheet**

Part Number: CTN380STD



Convoluted Tubing, Slit, .38" Dia, PA6, Black with Gray Stripe, 1900ft/carton

| Article Number      | 169-60015   |
|---------------------|---|
| Туре                | CTN380  |
| Color               | Black with Gray Stripe (BKSTGY)   |
| Features & Benefits | • Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture • Tubing protects cables and wires against automotive fluids, vibration wear • Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight |
| Quantity Per        | carton  |

| Product Description           | HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing,<br>provides an efficient method of routing and protecting wire harness<br>assemblies, while reducing the chance of installation damage. With a split<br>down the side where you can insert your wire harness, you can just easily<br>install Convoluted Tubing without removal of the entire assembly. It can also<br>serve to protect valuable hoses and cables. Convoluted tubing offer's excellent<br>protection against vibration wear, water, snow, ice and the effects of heat, cold<br>and sunlight on cables and wires. |
|-------------------------------|---|
| Short Description             | Convoluted Tubing, Slit, .38" Dia, PA6, Black with Gray Stripe, 1900ft/carton   |
| Global Part Name              | CTN380-PA6-BK   |
| Technical Description         | Convoluted Tubing, Slit, 3/8" Dia., PA6, Black w/Gray Stripe  |
|                               |   |
| Length L (Imperial)           | 1900.0  |
| Length L (Metric)             | 579.1   |
| Inner Diameter D (Imperial)   | 0.380   |
| Inner Diameter D (Metric)     | 9.65  |
| Diameter D (imperial)         | 0.526   |
| Diameter D (metric)           | 13.36   |
| Outside Diameter OD(Imperial) | 0.526   |
| Outside Diameter OD(metric)   | 13.36   |
| Nominal Diameter (Imperial)   | 0.375   |
| Nominal Diameter (Metric)     | 9.53  |

| Wall Thickness WT (Imperial)   | .005                              |
|--------------------------------|-----------------------------------|
| Wall Thickness WT (Metric)     | 0.127                             |
|                                |                                   |
|                                |                                   |
| Material                       | Polyamide 6 (PA6)                 |
| Material Shortcut              | PA6                               |
| Flammability                   | UL 94 HB                          |
| Halogen free                   | Νο                                |
| Operating Temperature (Metric) | -40°F to +300°F (-40°C to +149°C) |
| Reach Complaint(Article 33)    | Yes                               |
| ROHS Complaint                 | Yes                               |
|                                |                                   |
| Package Quantity(Imperial)     | 1900                              |
| Package Quantity (Metric)      | 579.10                            |
| Customs Number                 | 3926909987                        |

© 2018 HellermannTyton. All rights reserved.