

# Micro USB to USB OTG Host Adapter Cable, 5-Pin Micro USB B to USB A M/F, 6-in.

### MODEL NUMBER: U052-06N





#### **Highlights**

- Connect Thumb Drives,
   Keyboards, etc to OTG Tablets
   and Phones
- Plug-n-Play...No Software or Drivers Required

#### **System Requirements**

USB OTG enabled Tablet,
 SmartPhone, or other OTG
 mobile device

#### **Package Includes**

• U052-06N USB OTG Adapter

Connect a USB OTG ready Tablet or Smartphone to USB 2.0 Devices

## Description

Tripp Lite U052-06N, USB OTG Adapter, is the perfect solution for expanding the capabilities of an OTG enabled SmartPhone, Tablet, or other OTG devices, by directly connecting to USB peripherals, such as a USB thumb drive or a USB keyboard and mouse. Add a USB hub to the adapter to create additional ports to connect multiple USB devices. USB OTG technology makes this connection easy, and does not require drivers or software...Plug-n-Play! Connect the adapter to the Micro-B port on an OTG enabled mobile device, and then connect the USB device directly to the USB A port on the adapter for immediate use.

#### **Features**

- Micro USB Male to standard USB "A" Female On-The-Go ( OTG ) adapter
- Plug-n-Play...No Drivers or Software required
- Connect one USB device, or add a multi-port hub for multiple USB device connections
- 6inch length allows for flexible access for attached peripherals

# **Specifications**

OVERVIEW	
UPC Code	037332184375
Technology	USB 2.0 (High Speed); USB (all versions)
INPUT	
Cable Length (ft.)	0.5





	T	
Cable Length (m)	0.2	
Cable Length (in.)	6	
Cable Length (cm)	15.24	
PHYSICAL		
Wire Gauge (AWG)	28/24	
Shipping Dimensions (hwd / in.)	7.00 x 3.00 x 0.50	
Shipping Dimensions (hwd / cm)	17.78 x 7.62 x 1.27	
Shipping Weight (lbs.)	0.04	
Shipping Weight (kg)	0.02	
Material of Construction	PVC	
Color	Black	
Cable Outer Diameter (OD)	4.5MM	
Cable Jacket Rating	VW-1	
ENVIRONMENTAL		
Operating Temperature Range	14 to 140 F (-10 to 60 C)	
Storage Temperature Range	-4 to 185 F (-20 to 85 C)	
Relative Humidity	10% to 85%, Non-Condensing	
CONNECTIONS		
Side A - Connector 1	USB A (FEMALE)	
Side B - Connector 1	MICRO-USB B (MALE)	
Connector Plating	Nickel	
Contact Plating	Gold	
FEATURES & SPECIFICATIONS		
USB Specification	USB 2.0 (up to 480 Mbps)	
CERTIFICATIONS		
Certifications	Tested to CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

https://www.tripplite.com/products/product-certification-agencies