

## **Specification Sheet**

Part Number: 181-13008



Slotted Wall Wiring Duct, 1" X 3", Non-Adhesive, PVC, White, 120ft/Carton

Article Number	181-13008
Туре	SL1X3
Color	White (WH)
Features & Benefits	• Strong fingers prevent unwanted breaking. • Fingers are easily deflected outward, allowing ready positioning of the wires within the slotted wall duct. • Restricted opening design in the finger of the duct helps keep wires in place. • Restricted opening prevents unintended removal of wires and permits any individual wire to be traced without disconnection.
Quantity Per	carton
Product Description	Pro-Duct slotted wall wiring duct features break-away fingers which provide

cut for joints and Ts.

additional access for wire leads. Each section of the duct is provided with two score lines. The upper score line is used to break away fingers when a greater opening is required. The lower score line allows the sidewall to be smoothly

Short Description	Slotted Wall Wiring Duct, 1" X 3", Non-Adhesive, PVC, White, 120ft/Carton
Global Part Name	SL1X3-PVC-WH
Technical Description	Non-Adhesive
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	1.0
Width W (Metric)	25.4
Height H (Imperial)	3.07
Height H (Metric)	77.90
Mounting Hole Centers (Imperial)	4.0
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	Self-Extinguishing
Halogen free	No
Operating Temperature (Metric)	+122°F (+50°C)

Reach Complaint(Article 33)	No
ROHS Complaint	Yes
Certification/Specification WEB	CSA EN 50085-2-3_1A EN 50085-1:2005 + A1:2013 UL
UL Recognized (US)	Yes
Package Quantity(Imperial)	120
Package Quantity (Metric)	36.58
Customs Number	3925900000

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

 $<sup>\</sup>hbox{@}$  2018 HellermannTyton. All rights reserved.